

GEHL®

V420 SKID LOADER

PREVIEW



KEY FEATURES

- ✓ Multiple Track Widths and Tread Patterns
- ✓ Control Choices: T-bar, Pilot Joystick, Hand/Foot, and Pilot Dual-Hand
- ✓ IdealTrax Automatic™ Track Tensioning
- ✓ High-Flow Auxiliary Hydraulics Available
- ✓ Swing-out Cooler

KEY SPECIFICATIONS

- ✓ 4,200lbs. (1906 kg) Rated Operating Capacity
- ✓ 120 hp (90 kW) @ 2200 Deutz Engine
- ✓ 143.6" (3547 mm) Height to Hinge Pin
- ✓ 79.5" (2019 mm) Overall Machine Width
- ✓ 11,900 lbs. (5398 kg) Operating Weight

SPECIFICATIONS

DIMENSIONS	Overall Operating Height - Fully Raised (mm)	186.8" (4745)
	Height to Hinge Pin - Fully Raised (mm)	143.6" (3647)
	Overall Height to Top of ROPS (mm)	82" (2083)
	Overall Length with Bucket (mm)	158.5" (4026) w/84" Bucket
	Dump Angle at Full Height	31°
	Dump Height (mm)	114.8" (2916)
	Dump Reach at Full Height (mm)	39.5" (1003)
	Rollback at Ground	31°
	Rollback Angle at Full Height	100°
	Seat to Ground Height (mm)	41.2" (1046)
	Wheelbase (mm)	54.6" (1387)
	Overall Width - Less Bucket (mm)	79.5" (2019)
	Bucket Width (mm)	84" (2134)
	Ground Clearance to Chassis (mm)	7.3" (185)
	Overall Length - Less Bucket (mm)	121.5" (3086)
	Departure Angle	19°
	Clearance Circle - Front w/ Bucket (mm)	88.5" (2248)
	Clearance Circle - Front w/o Bucket (mm)	50.8" (1290)
Clearance Circle - Rear (mm)	70.5" (1791)	
Standard Specification Tire Size	14.00x17.5 HD	
CAPACITY / WEIGHTS	Rated Operating Capacity (kg)	1,050 lbs. (476)
	Rated Op. Capacity with Opt. Counterweight (kg)	1,175 lbs. (533)
	Fuel Tank (L)	10.4 gal. (39.4)
	Travel Speed - Maximum (km/hr)	5.9 mph (9.5)
	Operating Weight - Approximate (kg)	4000 lbs. (1814)
ENGINE	Make	Deutz
	Model	TCD 3.6 Tier IV
	Gross Power (kW) @ rpm	120 hp (74) @ 2200
	Net Power (kW) @ rpm	97.2 hp (72.5) @ 2200
	Maximum Torque (Nm) @ rpm	354 ft.-lbs. (442) @ 1600
	Displacement (L)	220 cu. in. (3.6)
ELECTRICAL SYSTEM	Battery (CCA)	12-volt (675)
	Starter (kW)	12-volt (2.3)
	Alternator	130-amp
HYDRAULICS	Auxiliary Hydraulics - Standard (L/min)	32 gpm (121)
	High-Flow Auxiliary Hydraulics - Option (L/min)	40.8 gpm (185.5)
	Reservoir Capacity (L)	16.75 gal. (63.4)



STANDARD FEATURES

- All-Tach® Attachment Mounting System
- Anti-Vandalism Protection
- Auxiliary Hydraulics
- Brake Control (Auto / Manual)
- Color Display with Full Instrumentation
- Engine Auto-Shutdown System
- High-Back Adjustable Seats
- Foot and Hand Throttles
- Horn
- Hydraloc™ Safety System
- Hydrostatic Drive - Servo
- Integral Access Plate (removable)
- Lift Arm Support Device
- Operator Restraint Bar
- ROPS/FOPS Level II Overhead Guard
- Sound Reduction Material
- Swing-Out Cooler
- Two Speed Drive
- Work Lights - Front and Rear

OPTIONAL FEATURES

- Air Conditioning
- Back-Up Alarm
- Cab Enclosure
- Controls: Dual-Hand, Gehl T-Bar, Hand/Foot, Pilot Operated Joystick
- Counterweight
- Engine Block Heater
- Heating
- High-Flow Auxiliary Hydraulics
- Hydraulic™ Ride Control
- Power-A-Tach™ Attachment Mounting System
- Selectable Self-Leveling Hydraulic Lift Action
- Suspension Seat - Air Ride
- Suspension Seat - Mechanical
- Two-Speed Drive


SPECIFICATIONS ARE PRELIMINARY

Gehl reserves the right to add improvements or make changes in features and specifications at any time without notice or obligation.

Gehl reminds users to read and understand the operator's manual before operating any equipment. Also, make sure all safety devices and shields are in place and functioning properly.



One Gehl Way, West Bend, WI 53095



Phone: (262) 334-9461