

V210 - NEW

SKID LOADERS



GEHL®

Capacities		Metric
Operating Capacity At 50% Tipping Load		952.54 kg
Rated Operating Capacity with Optional Counterweight		1021 kg
Operating Weight		3393 kg
Unladen weight		3045 kg
Tipping capacity		1905 kg
Weight and dimensions		
Operating Weight - Approximate		3393 kg
Overall Operating Height - Fully Raised	h27	4013 mm
Height to Hinge Pin – Fully Raised	h28	3061 mm
Overall Height to Top of ROPS	h17	2032 mm
Dump angle at full height	a5	42 °
Dump height	h29	2286 mm
Overall length with bucket	l16	3543 mm
Dump reach - Full height	r6	851 mm
Rollback Angle at Full Height	a4	92 °
Seat to ground height	h30	952.50 mm
Overall width less bucket	b1	1623 mm
Ground clearance	m4	178 mm
Overall length - Less Bucket	l2	2743 mm
Clearance Radius - Front with Bucket	b18	2146 mm
Clearance Circle - Rear	wa1	1664 mm
Performances		
Travel Speed with Two-Speed Option - Maximum		18.70 km/h
Travel speed (unladen)		12.10 km/h
Wheels		
Transmission type		Hydrostatic
Engine		
Engine brand		Yanmar
Engine model		4TNV98C-NGL
Engine norm		Stage V
Gross Power (kW)		51.70 kW
Net Power (kW)		52.70 kW
Max. torque / Engine rotation		241 Nm / 1625 rpm
Number of cylinders		4
Engine cooling system		Water
Battery		12 V
Alternator - Ampere		100 A
Starter (kW)		3 kW
Hydraulics		
Standard flow - Auxiliary hydraulics		86.50 l/min
Auxiliary Hydraulic Pressure		239.59 bar
High-Flow Auxiliary Hydraulics – Option		114 l/min
High-Flow Auxiliary Hydraulics Pressure – Option		229.25 bar
Tank capacities		
Fuel tank		106 l
Reservoir Capacity Hydraulics		22.70 l
Displacement		3.30 l



GEHL®

Siège Social
P.O. Box 179 - One Gehl Way - West Bend, WI, USA 53095
Tel: (262) 334-9461 - Fax: (262) 338-7517
www.gehl.com



This brochure describes versions and configuration options for Gehl products which may be fitted with different equipment. The equipment described in this brochure may be standard, optional or not available depending on version. Gehl reserves the right to change the specifications shown and described at any time and without prior warning. The manufacturer is not liable for the specifications given. For more information, contact your Gehl dealer. Non-contractual document. Product descriptions may differ from actual products. List of specifications is not comprehensive. The logos and visual identity of the company are the property of Gehl and may not be used without authorization. All rights reserved. The photos and diagrams contained in this brochure are provided for information only.

MANITOU EQUIPMENT AMERICAS, LLC - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS West Bend