SKID LOADERS



GEHL®

Capacities		Metric
Operating Capacity At 50% Tipping Load		1043.26 kg
Operating Weight		3497 kg
Inladen weight		3150 kg
ipping capacity		2086.53 kg
Veight and dimensions		2000.33 kg
Operating Weight - Approximate		3497 kg
Overall Operating Height - Fully Raised	h27	4039 mm
leight to Hinge Pin – Fully Raised	h28	3086 mm
Iverall Height to Top of ROPS	h17	2058 mm
- ,	a5	2058 HIIII 42 °
ump angle at full height	h29	2312 mm
nump height		2312 mm 3589 mm
verall length with bucket	116	
Dump reach - Full height	r6	826 mm
tollback Angle at Full Height	a4	92 °
eat to ground height	h30	978 mm
Overall width less bucket	b1	1707 mm
round clearance	m4	203 mm
Overall length - Less Bucket	12	2789 mm
learance Radius - Front with Bucket	b18	2171 mm
learance Circle - Front without Bucket	b19	1308 mm
learance Circle - Rear	wa1	1689 mm
Performances		
ravel Speed with Two-Speed Option - Maximum		20 km/h
ravel speed (unladen)		12.70 km/h
Vheels		
ransmission type		Hydrostatic
ngine ngine		
ngine brand		Yanmar
ngine model		4TNV98CT-XNGL
ngine norm		Stage V
ross Power (kW)		53.70 kW
et Power (kW)		52.70 kW
Max. torque / Engine rotation		294 Nm / 1800 rpm
lumber of cylinders		4
ngine cooling system		Water
attery		12 V
llternator - Ampere		100 A
tarter (kW)		3 kW
lydraulics		
tandard flow - Auxiliary hydraulics		86.50 l/min
uxiliary Hydraulic Pressure		239.59 bar
igh-Flow Auxiliary Hydraulics – Option		114 l/min
ligh-Flow Auxiliary Hydraulics Pressure – Option		229.25 bar
ank capacities		
uel tank		106 l
Displacement		3.30 l
•		





Siège Social P.O. Box 179 - One Gehl Way - West Bend, WI, USA 53095 Tel: (262) 334-9461 - Fax: (262) 338-7517 www.gehl.com



This brochure describes versions and configuration options for Gehl products which may be fitted with different equipment. The equipment described in this brochure may be standard, optional or not available depending on version. Gehl reserves the right to change the specifications shown and described at any time and without prior warning. The manufacturer is not liable for the specifications given. For more information, contact your Gehl dealer. Non-contractual document. Product descriptions may differ from actual products. List of specifications is not comprehensive. The logos and visual identity of the company are the property of Gehl and may not be used without authorization. All rights reserved. The photos and diagrams contained in this brochure are provided for information only.

MANITOU EQUIPMENT AMERICAS, LLC - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS West Bend